FOUR RIVERS SANITATION AUTHORITY

CONSTRUCTION ADMINISTRATION PARKING LOT AND HOUSEHOLD HAZARDOUS WASTE SITES CAPITAL IMPROVEMENT PROJECT #2217


2024

BOARD OF TRUSTEES

RICHARD T. POLLACK PRESIDENT
BENJAMIN W. BERNSTEN VICE-PRESIDENT
GINGER HAAS CLERK/TREASURER
ELMER JONES TRUSTEE
RICHARD MOWRIS TRUSTEE

OFFICIALS

TIMOTHY S. HANSON EXECUTIVE DIRECTOR
CHRISTOPHER T. BAER, PE DIRECTOR OF ENGINEERING



INDEX OF SHEETS

Sheet Number	Sheet Title
COVER	COVER
G001	LEGEND GENERAL NOTES & SUM OF QTYS
C100	EXISTING CONDITIONS & REMOVALS PLAN
C101	SITE LAYOUT PLAN
C102	SITE GRADING PLAN
C103	SITE UTILITY PLAN
C104	EROSION CONTROL PLAN
C105	TEMPORARY EROSION CONTROL DETAILS
C106	PROJECT DETAILS
C107	LANDSCAPE PLAN
C108	COLLECTION SYSTEMS ADMINISTRATION LAYOUT PLAN
C109	COLLECTION SYSTEMS ADMINISTRATION GRADING PLAN

IDOT STANDARD DETAILS:

280001-07 TEMPORARY EROSION CONTROL SYSTEMS
606001-08 CONCRETE CURB TYPE B
701006-05 OFF-RD OPERATIONS FROM 15' TO 24" FROM PAVEMENT EDGE
701301-04 LANE CLOSURE SHORT TIME OPERATIONS


701502-09 URBAN LANE CLOSURE WITH BIDIRECTIONAL LEFT TURN LANE

701801-06 SIDEWALK, CORNER, OF CROSSWALK CLOSURE

701901-09 TRAFFIC CONTROL DEVICES







GENERAL NOTES

- 1. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR THE EXECUTION OF WORK TO THE LINES AND GRADES SHOWN ON THE PLANS. CONSTRUCTION SHALL NOT VARY FROM THE PLANS WITHOUT PRIOR APPROVAL FROM THE FOUR RIVERS SANITATION AUTHORITY (FRSA).
- 2. THE CONTRACTOR SHALL NOTIFY THE FRSA, MUNICIPAL AGENCIES, JURISDICTIONAL ROADWAY AUTHORITIES AND ALL AFFECTED PROPERTY OWNERS A MINIMUM OF 48 HOURS PRIOR TO START OF CONSTRUCTION.
- 3. THE CONTRACTOR SHALL IDENTIFY ALL UTILITY LOCATIONS IN THE FIELD BY CONTACTING J.U.L.I.E. AT 811 OR 1-800-892-0123 AND ALL UTILITIES NOT ON THE J.U.L.I.E. NETWORK 48 HOURS, MINIMUM, PRIOR TO START OF CONSTRUCTION.
- 4. ALL ROADWAY CONSTRUCTION SHALL BE COMPLETED IN ACCORDANCE WITH THE REQUIREMENTS OF THE ROADWAY AUTHORITY, THE IDO STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, LATEST EDITION, AND THE FOUR RIVERS SANITATION AUTHORITY.
- 5. THE CONTRACTOR SHALL COMPLY WITH ALL REQUIREMENTS OF THE ILLINOIS URBAN MANUAL FOR SOIL EROSION AND SEDIMENT CONTROL
- 6. PROTECTION OF WATER SUPPLIES SHALL BE IN ACCORDANCE WITH TITLE 35, C, SECTION 370.350 OF THE ILLINOIS RECOMMENDED STANDARDS FOR SEWAGE WORKS.
- 7. ALL STRUCTURES, INLETS, PIPES, SWALES, AND PAVEMENT MUST BE KEPT CLEAN AND FREE OF DIRT AND DEBRIS AT ALL TIMES.
- 8. THE CONTRACTOR IS RESPONSIBLE FOR MAINTAINING ADEQUATE SIGNS, BARRICADES, FENCING, TRAFFIC CONTROL DEVICES AND MEASURES, AND ALL OTHER MEASURES THAT ARE NECESSARY TO PROTECT THE SAFETY OF THE SITE AT ALL TIMES.
- 9. PROPERTY CORNERS MUST BE CAREFULLY PROTECTED UNTIL THEY HAVE BEEN REFERENCED BY A PROFESSIONAL LAND SURVEYOR.

SPECIAL CONSIDERATIONS

- I. PROJECT ACCESS WILL BE ALLOWED OFF OF MARTIN ROAD.
- THE CONTRACTOR SHALL OBTAIN A CITY OF ROCKFORD RIGHT-OF-WAY NCROACHMENT PERMIT PRIOR TO STARTING ANY WORK. THE ONTRACTOR SHALL PAY ALL ASSOCIATED FEES AND SUBMIT ALL REQUIRED BOND AND INSURANCE INFORMATION TO THE CITY FOR APPROVAL. COPIES OF ALL CITY PERMITS, INCLUDING PROOF OF INSURANCE AND BOND, SHALL BE SUBMITTED TO THE FRSA UPON RECEIPT BY THE CONTRACTOR. ALL COSTS ASSOCIATED WITH CITY OF ROCKFORD PERMITS SHALL BE AT NO ADDITIONAL COST TO THE FRSA.

SUMMARY OF QUANTITIES

No.	ITEM	UNIT	QTY.
1	HMA SRF CSE IL 9.5 MIX "D" N50, 2"	TON	412
2	HMA BDR CSE IL 19.0 N50, 4"	TON	823
3	PAVEMENT MARKING - LINE 4"	FOOT	511
4	PAVEMENT MARKINGS - SYMBOLS	EACH	2

THIS PLAN SET CONTAINS INFORMATION FOR THE COMPLETE PROJECT. WORK UNDER THIS BID INCLUDES FINAL SHAPING OF AGGREGATE, HMA PAVING OPERATIONS, AND PAVEMENT MARKINGS. OTHER INFORMATION SHOWN WITHIN PLAN SET TO BE BY OTHERS AND FOR INFORMATION ONLY

UTILITIES

NICOR (GAS) SAKIBUL FORAH (815) 388-2903

FRONTIER (COMMUNICATIONS)

COMED (ELECTRIC) **AMIR MAHMUTAGIC** (630) 437-2212

ILLINOIS FIBER RESOURCES LANCE SANDY (815) 753-6075

AT&T (COMMUNICATIONS) **HECTOR GARCIA** (630) 573-5465

CITY OF ROCKFORD-WATER DIV. JAMIE ROTT (779) 348-7654

COMCAST (COMMUNICATIONS) KEITH KOSHINSKI (224) 229-5432

CITY OF ROCKFORD-ENGINEERING TIMOTHY HINKENS (779) 348-7300

HOT-MIX ASPHALT MIXTURE **REQUIREMENTS**

MIXTURE USE(S)	SURFACE COURSE	BINDER COURSE		
PG:	PG 64-22	PG 64-22		
DESIGN AIR VOIDS	4.0 @ N50	4.0 @ N50		
MIXTURE COMPOSITION (GRADATION MIXTURE)	IL 9.5	IL 19.0		
FRICTION AGGREGATE	MIX "D"	N/A		
MIX UNIT WEIGHT	112 lbs/sy/in	112 lbs/sy/in		
QUALITY MGMT PROGRAM	QC/QA	QC/QA		
THESE MIXTURE REQUIREMENTS ARE APPLICABLE FOR THIS PROJECT				

Four Rivers Sanitation Authority


HOUSEHOLD HAZARDOUS WASTE SITE **CAPITAL IMPROVEMENT PROJECT #2217**


LEGEND GENERAL NOTES & SUM OF QTYS


Sheet No. G001


FOR BID


Date: 05/21/2024


















SHEET 1 OF 2

DATE 8-18-94

Date

Designed :



EROSION CONTROL NOTES

GENERAL NOTES

THE ESTIMATED AREA OF DISTURBANCE FOR THIS PROJECT IS <u>LESS THAN 1 ACRE</u>. THEREFORE, A NOTICE OF INTENT (NOI) WILL NOT BE FILED. AN EROSION CONTROL PLAN HAS BEEN PREPARED FOR THIS PROJECT. THE CONTRACTOR SHALL COMPLY WITH ALL APPLICABLE REQUIREMENTS OF THE ILLINOIS URBAN MANUAL, CURRENT EDITION, IDOT STANDARD SPECIFICATIONS FOR ROAD AND BRIDGE CONSTRUCTION, CURRENT EDITION, THE FOUR RIVERS SANITATION AUTHORITY (FRSA), AND THE PROJECT SPECIFICATIONS AND DETAILS.

THE EROSION CONTROL DEVICES, MATERIALS AND PROCEDURES SHOWN IN THESE PLANS ARE TO BE CONSIDERED A MINIMUM. ADDITIONAL DEVICES OR MATERIALS MAY BE REQUIRED BASED ON EXISTING SITE CONDITIONS, AT THE DIRECTION OF THE ENGINEER. ANY DEVICES, MATERIALS, OR PROCEDURES REQUIRED BY THE ENGINEER DUE TO THE CONTRACTOR'S ACTIONS OR NEGLIGENCE WILL BE AT NO ADDITIONAL COST TO THE FRSA.

ALL DISTURBED AREAS SHALL BE SEEDED UNLESS AGRICULTURAL OR OTHERWISE NOTED ON THE PLANS. THE CONTRACTOR IS RESTRICTED TO WORK IN TEMPORARY EASEMENTS OR WORK AREAS DELINEATED ON PLANS. THE CONTRACTOR SHALL TAKE WHATEVER ACTIONS AND MEASURES ARE DEEMED NECESSARY BY THE FRSA OR AUTHORIZED AGENCY TO ELIMINATE EXCESSIVE SILTATION OR EROSION AND TO STABILIZE THE PROJECT AREA. DISCHARGE OF HAZARDOUS SUBSTANCES INTO STORM WATER IS SUBJECT TO IEPA REPORTING AND CLEANUP REQUIREMENTS.

CONTROL MEASURES

EROSION AND SEDIMENT CONTROL MEASURES SHALL BE IN PLACE BEFORE CONSTRUCTION IN EACH AREA, AS DETERMINED BY THE ENGINEER, AND SHALL BE MAINTAINED THROUGHOUT CONSTRUCTION. CONSTRUCTION ACTIVITIES SHALL ENSURE THAT EXISTING VEGETATION IS PRESERVED WHERE PRACTICAL. THE FOLLOWING CONTROLS WILL BE PROVIDED AS A MINIMUM FOR THE DURATION OF THIS PROJECT:

- SEDIMENT CONTROL SHALL BE PROVIDED DOWNSLOPE OF ALL STOCKPILE AREAS.
- STABILIZED CONSTRUCTION ENTRANCES MUST BE INSTALLED AS DETAILED AND WHERE REQUIRED BY THE ROADWAY AUTHORITY OR FRSA.
- INLET PROTECTION MUST BE INSTALLED FOR ALL INLETS THAT COULD BE SUBJECT TO SILTATION, AS DETERMINED BY THE ENGINEER.
- ALL ROADWAYS SHALL BE KEPT CLEAN OF DEBRIS, MUD, SOIL, AND CONSTRUCTION MATERIALS AND SHALL BE INSPECTED AT THE END OF EACH DAY AND CLEANED AS NECESSARY.
- ALL DISTURBED AREAS MUST BE STABILIZED WITHIN 7 DAYS IF THEY ARE TO REMAIN DISTURBED FOR MORE THAN 14 DAYS.


MAINTENANCE

CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTENANCE AND REPAIR OF ALL EROSION AND SEDIMENT CONTROL DEVICES AND PROTECTIVE MEASURES AS REQUIRED TO MAINTAIN THE INTENDED FUNCTION. SEDIMENT COLLECTED FROM THE CONSTRUCTION SITE SHALL BE DISPOSED OF ON THE SITE ON A REGULAR BASIS AS NEEDED. ANY DEBRIS OR SILT DEPOSITED IN THE FLOW LINE OF DRAINAGE STRUCTURES, DITCHES, ETC., THAT COULD OBSTRUCT FLOW SHALL BE REMOVED AT THE CLOSE OF EACH WORKING DAY. ALL DRAINAGE STRUCTURES SHALL BE FREE OF DIRT AND DEBRIS. THE CONTRACTOR SHALL REMOVE AND DISPOSE OF ALL TEMPORARY EROSION CONTROL DEVICES WITHIN 30 DAYS OF FINAL SITE STABILIZATION APPROVAL BY THE FRSA. THE SITE SHALL HAVE A MIN. OF 70% VEGETATIVE COVER TO BE CONSIDERED STABILIZED.

OTHER DISCHARGES

NON STORM WATER DISCHARGES INCLUDING WASHING OF VEHICLES, CONCRETE WASH-OUT, WATER FOR DUST CONTROL, AND TRENCH DEWATERING DISCHARGES SHALL BE DIRECTED AWAY FROM UNPROTECTED, BARE, OR UNSTABILIZED SOIL AND APPROPRIATE MEASURES SHALL BE IMPLEMENTED TO PREVENT EROSION OR RUNOFF FROM THE SITE. DEWATERING DISCHARGE MUST BE INTO SILT CONTAINMENT BAGS WITH PROPERLY ENGINEERED ANIONIC POLYMER AND FABRIC PORE SIZE. UNDER NO CIRCUMSTANCE SHALL DEWATERING DISCHARGE BE ALLOWED TO FLOW DIRECTLY INTO WATERWAYS. A DEWATERING DISCHARGE PLAN SHALL BE SUBMITTED TO THE FRSA FOR APPROVAL.


THIS PLAN SET CONTAINS INFORMATION FOR THE COMPLETE PROJECT.
WORK UNDER THIS BID INCLUDES FINAL SHAPING OF AGGREGATE, HMA
PAVING OPERATIONS, AND PAVEMENT MARKINGS. OTHER INFORMATION
SHOWN WITHIN PLAN SET TO BE BY OTHERS AND FOR INFORMATION ONLY.




REVISION

INT.

No. DATE








HOUSEHOLD HAZARDOUS WASTE SITE CAPITAL IMPROVEMENT PROJECT #2217

TEMPORARY EROSION CONTROL DETAILS

Sheet No. C105

FOR BID

ID Date: 05/21/2024



ADA PAVEMENT MARKING SYMBOL C106 NOT TO SCALE

THIS PLAN SET CONTAINS INFORMATION FOR THE COMPLETE PROJECT. WORK UNDER THIS BID INCLUDES FINAL SHAPING OF AGGREGATE, HMA PAVING OPERATIONS, AND PAVEMENT MARKINGS. OTHER INFORMATION SHOWN WITHIN PLAN SET TO BE BY OTHERS AND FOR INFORMATION ONLY.

CONCRETE WASHOUT DETAIL

AUTFICAD2006


30-MIL POLYETHYLENE

Letters 6" Min. Height ——

CONCRETE WASHOUT AREA

SIGN DETAIL

NOTES:



STRAW BALE

6" WIRE STAPLE OR SANDBAG

Plywood or Aluminum

__ 4"x4"x6' Wood Post or 6' Steel Post Min.

1. Maintaining temporary concrete washout facilities shall include removing and disposing of hardend concrete and/or slurry and

2. Facility shall be cleaned or reconstructed in a new area once

3. Each straw bale is to be staked in place using (2) 2"x2"x4'

TEMPORARY CONCRETE

/ASHOUT FACILITY — STRAW BALE checked...

returning the faciliities to a functional condition.

washout becomes two-thirds full.

48" X 24" Min.

6" Wire Staple or Sandbag —

<u>Liner Anchor</u>

STRAW BALE ANCHOR SECTIONS

30-Mil Polyethylene —

(ANCHOR EVERY 2')

<u>Plan view</u>

NOTE:
PROVIDE HAND TOOLED TRANSVERSE CONTRACTION JOINTS @ 5'-0" O.C. MAX., 1/2" EXPANSION JOINTS @ 50'-0" O.C. MAX.
COMPLYING WITH 424.07 OF IDOT STANDARD SPECIFICATIONS





No. DATE REVISION

HOUSEHOLD HAZARDOUS WASTE SITE **CAPITAL IMPROVEMENT PROJECT #2217**

PROJECT DETAILS

Sheet No. C106

Date: 05/21/2024

FOR BID

